



**PF 5051 "T" 500AL**

**PF 5051 "T" 500AL      FAT0500AL**

**Technische Spezifikationen**

Leuchtmittel	300/500W
Sockel	GY 9.5
Linse	Ø 150 mm Planconvex
Abstrahlwinkel	6-45°
Besondere Features	Spindelfokussierung
Gehäuse	Aluminium-Strangprofil + Stahlblech
Abmessungen	L 310 x B 270 x H 200 mm, (H 350 incl. Bügel)
Gewicht	4.2 kg

**Zubehör**

Schutzgitter	inclusive
Farbfilterrahmen	185 x 185 mm

**Technical specifications**

Light source	300/500W
Socket	GY 9.5
Lens	Ø 150 mm Planconvex
Beam angle	6-45°
Special features	Wormdrive beam adjustment
Housing	Aluminium diecast profile + steel sheets
Dimensions	L 310 x W 270 x H 200 mm, (H 350 incl. bracket)
Weight	4.2 kg

**Accessories**

Protection grille	included
Filterframe	185 x 185 mm



**PF 5053 "T" 500FR**

**PF 5053 "T" 500FR      FAT0500FR**

**Technische Spezifikationen**

Leuchtmittel	300/500W
Sockel	GY 9.5
Linse	Ø 150 mm Fresnel
Abstrahlwinkel	8-42°
Besondere Features	Spindelfokussierung
Gehäuse	Aluminium-Strangprofil + Stahlblech
Abmessungen	L 310 x B 270 x H 200 mm, (H 350 incl. Bügel)
Gewicht	3.7 kg

**Zubehör**

Schutzgitter	inclusive
Farbfilterrahmen	185 x 185 mm

**Technical specifications**

Light source	300/500W
Socket	GY 9.5
Lens	Ø 150 mm Fresnel
Beam angle	8-42°
Special features	Wormdrive beam adjustment
Housing	Aluminium diecast profile + steel sheets
Dimensions	L 310 x W 270 x H 200 mm, (H 350 incl. bracket)
Weight	3.7 kg

**Accessories**

Protection grille	included
Filterframe	185 x 185 mm